

LEMAITRE

Safety since 1974

LEVANTE S3S



New standard 2022:
Standard EN ISO 20345: 2022

Eco-designed
model



Sizes 35 to 49 Ref. LEVAS3SNR

Product Highlights



- Heavy duty boot available with men's and women's fit.
- 2,0 mm thick high strength leather (against abrasion, tearing and puncture). No side seams.
- Gusseted tongue sewn inside the shoe to limit water retention and facilitate cleaning
- Scuffcap TPU injected: extreme resistance at the front.
- Fluorescent insert: regenerated leather made from recycled material
- Insole with 77.5% recycled components
- Eco-designed safety shoe made from recycled materials and components > 25% recycled or reused materials (ISO 14021: 2016 standard).



- Protective toe cap: HDFC composite fiber.
- Puncture-resistant midsole: 78% recycled high tenacity composite fabric "0" penetration. PS type (3mm nail).



TRAILIUM PU2D antistatic sole

- 4 mm studs suitable for construction and heavy industry
- Drainage channels for liquids and mud to avoid the risk of aquaplaning
- Lateral edges and 15 mm raised heel: reinforced grip on ladder rungs
- Large footprint for optimum stability
- Arch support and heel cushioning: prevention of RSI

USE

- Construction, heavy industry
- Outdoor activities

Data sheet subject to change, non-contractual photos.



lemaitre-securite.com

Lemaitre takes care.



LEVANTE S3S



New standard 2022 :
Standard EN ISO 20345 : 2022

Characteristics of the upper

- **Upper material:** Water-repellent oiled split leather with anti-abrasion/anti-wear groove toe cap and heel
- **Tongue with inner gusset:** 90% recycled textile
- **Collar and quarters:** 90% recycled textile
- **Lining:** Air bamboo, 61% recycled materials (including 18% bamboo)
- **Laces:** 100% recycled

Characteristics of the sole

- **Designation:** TRAILIUM PU2D
- **Material:** polyurethane with recycled polyol
- **Antistatic sole**
- **Adhesion coefficient (fundamental requirements):**
forward heel slip: 0,38 (standard \geq 0,31)
backward forepart slip: 0,45 (standard \geq 0,36)
- **SR Adhesion coefficient:**
forward heel slip: 0,27 (standard \geq 0,19)
backward forepart slip: 0,37 (standard \geq 0,22)

VARIANT



Mistral S3S
MIST3SNR

Practical information

Weight of one shoe size 42 : 623 g

AET n° 0075/007/161/07/23/1095 EXT 02/07/23

AET n° 0075/007/161/07/23/1095 EXT 01/07/23

Packaging

Size 35 to 44

shoebox 351 x 232 x 122 mm

carton 635 x 445 x 315 mm

10 shoeboxes per carton

Size 45 to 49

shoebox 361 x 292 x 130 mm

carton 660 x 450 x 360 mm

10 shoeboxes per carton

Gencods

35	3237154532355	43	3237154532430
36	3237154532362	44	3237154532447
37	3237154532379	45	3237154532454
38	3237154532386	46	3237154532461
39	3237154532393	47	3237154532478
40	3237154532409	48	3237154532485
41	3237154532416	49	3237154532492
42	3237154532423		

Memo for basic and additional requirements of the standard EN ISO 20345:2022

Safety Footwear

S3S



Sliding test

No marking **Fundamental requirements**
Slip-resistant shoe on a tiled floor with a solution of sodium lauryl sulfate (NaLS).



Shoe resistant to slipping on a tiled floor with glycerin.



200 J toe cap: Protection of the forefoot against shocks and crushing



Non-metallic puncture-resistant midsole resistant with a 3 mm point (type PS)

A	Anti-static shoes	Ci	Insulation against cold
E	Shock absorption at the heel	Hi	Insulation against heat
Fo	Fuel oil-resistant outsole	Hro	Outsole resistance to hot contact
Wpa	Water penetration and water absorption resistant upper	Wr	Water resistant
SC	Abrasion resistant scuff cap	LG	Ladder grip system
ESD	Electrostatic discharge	An	Ankle protection

Lemaitre Sécurité
17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

LEMAITRE

Safety since 1974

lemaitre-securite.com

DON_LS 04 TDS 0166
update: 18/01/24

Member of
SINAMAP

