

Code	PB26-BLK
Standard	EN ISO 20349-1:2017 + A1:2020 S3 HRO HI CI SRC
Name / Description	Mid Length Foundry Boot
Weight	850 grams
Colour	Black
Sizes	5 6* 7 8 9 10* 11 12 13
Properties	Upper: Full Grain Leather with Special Heat Resistant properties. (Leather 1.8-2.0mm). Inner Lining: Moisture Wicking Textile. Toe Cap: Steel Toe Cap Resistant to 200J. Midsole: Stainless Steel Midsole – Min. 1100N. Sole Unit: Dual Density Rubber/Rubber Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed. Additional Features: Para Aramid Flame resistant stitching, Velcro Quick Release Fastening.
Areas of Application	The PB26 is suitable for use in foundry environments where there is a high risk of it coming into contact with molten metal. Made using only full grain leather, Para Aramid stitching and a textile lining, this product is highly flame resistant and can be used for a variety of foundry and welding applications.
Standard	EN ISO 20349-1:2017 + A1:2020 CI SRC Fe Cat. 3 S3 HRO CI SRC Fe PRODUCT PERFORMANCE PASSION
Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
Symbols	
Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk