

BRIMIR S3 Vibram®



Standard EN ISO 20345: 2011



LEMAITRE

Safety since 1974



WATER RESISTANT

UTURN® lacing system

- quick lacing
- made of durable nylon
- precision and adjustment

Waterproof breathable membrane lining

- 100% waterproof, breathable and anti-bacterial
- optimal ventilation of the foot
- improved comfort
- full upper fitting

Sizes 35 to 49

Ref. BRIMS30NR

Product Highlights



- Ranger available with a men's and women's fit.



- Ankle protection by Lemaitre, malleolus protection against side impacts.



- 2.0 mm thick high strength leather (against abrasion, tearing and puncture). Tongue with split leather gusset to prevent any infiltration of dust/stones.

- Scuffcap TPU injected: extreme resistance at the front.

- Memory Foam Titan sole for immediate and lasting comfort: antibacterial properties, respects foot hygiene.



- Protective toe-cap: composite HDFC.



- Puncture-resistant midsole: high tenacity fabric "0" penetration.



TRAIL VIBRAM® sole PU/antistatic nitrile rubber.



- Exclusive technical sole developed in partnership with Vibram®.

- Semelle Outdoor with excellent grip, Hi, HRO, adapted to difficult climatic conditions (hot and cold).

- Excellent abrasion resistance.

- Raised heel (15 mm height) for improved safety, especially on ladders.

USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, oil platform



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



BRIMIR S3 Vibram®



Standard EN ISO 20345: 2011

Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with abrasion-resistant TPU scuffcap material
- **Tongue/gusset:** water-repellent leather
- **Collar:** water-repellent leather
- **Lining:** imper-breathing membrane

Characteristics of the sole

- **Designation:** TRAILIUM VIBRAM®
- **Material:** polyurethane / PU - caoutchouc nitrile - Vibram® antistatique
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,43 (standard ≥ 0,32)
forward heel slip: 0,42 (standard ≥ 0,28)
- **SRB Adhesion coefficient:**
forward flat slip: 0,23 (standard ≥ 0,18)
forward heel slip: 0,19 (standard ≥ 0,13)

VARIANT



Tyr S3 SRC
TYRS30NR

Practical information

Women fitting 35-39

Weight of one shoe size 38:
855 g

Men fitting 40-49

Weight of one shoe size 42:
935 g

Gencods

35	3237154407356	43	3237154407431
36	3237154407363	44	3237154407448
37	3237154407370	45	3237154407455
38	3237154407387	46	3237154407462
39	3237154407394	47	3237154407479
40	3237154407400	48	3237154407486
41	3237154407417	49	3237154407493
42	3237154407424		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



SRC = SRA + SRB

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



LEMAITRE

Safety since 1974

DON_LS 04 TDS 0023
update: 04/12/20

Member of
SYNAMAP

