

# FINN S3



Standard EN ISO 20345 : 2011



**LEMAITRE**

*Safety since 1974*



### UTURN® lacing system

- quick lacing
- made of durable nylon
- precision and adjustment

Size 35 to 49

Ref. FINNS30NR

## Product Highlights



- **Low shoe available with men's and women's fit.**



- **2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

- **Scuffcap TPU injected:** extreme resistance at the front.

- **Memory Foam Titan sole for immediate and lasting comfort:** antibacterial properties, respects foot hygiene.



- **Protective toe-cap:** composite HDFC.



- **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



## TRAILIUM PU2D antistatic sole

- **4 mm studs** suitable for construction and heavy duty industry
- **Drainage channels for liquids and mud** to avoid any risk of aquaplaning
- **Lateral edges and 15mm raised heel:** reinforced grip on ladder rungs
- **Large bearing surface,** optimal stability
- **Arch support and heel cushioning:** MSD prevention

## USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



[lemaitre-securite.com](http://lemaitre-securite.com)

An exacting attitude to quality is our culture, safety our priority



# FINN S3



Standard EN ISO 20345 : 2011

## Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with abrasion-resistant TPU scuffcap material
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** 3D microporous fabric

## Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**  
forward flat slip: 0,34 (standard  $\geq 0,32$ )  
forward heel slip: 0,31 (standard  $\geq 0,28$ )
- **SRB Adhesion coefficient:**  
forward flat slip: 0,20 (standard  $\geq 0,18$ )  
forward heel slip: 0,17 (standard  $\geq 0,13$ )

## VARIANT



**Forseti S3 SRC**  
FORSS30NR

## Practical information

### Women fitting 35-39

Weight of one shoe size 38:  
550 g

### Men fitting 40-49

Weight of one shoe size 42:  
630 g

## Gencods

35	3237154408353	43	3237154408438
36	3237154408360	44	3237154408445
37	3237154408377	45	3237154408452
38	3237154408384	46	3237154408469
39	3237154408391	47	3237154408476
40	3237154408407	48	3237154408483
41	3237154408414	49	3237154408490
42	3237154408421		

## Memo for basic and additional requirements of the standard EN ISO 20345: 2011

### Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



$SRC = SRA + SRB$

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024  
F - 67350 Val de Moder  
Tél. +33 (0)3 88 72 28 80

[lemaitre-securite.com](http://lemaitre-securite.com)



**LEMAITRE**

Safety since 1974

DON\_LS 04 TDS 0027  
updated: 04/12/20

Member of  
**SINAMAP**

