

NJORD S3



Standard EN ISO 20345 : 2011



LEMAITRE

Safety since 1974



Ankle protection by Lemaitre


Malleolus protection against side impacts

Sizes 35 to 49

Ref. NJORS30NR

Product Highlights

 **Heavy duty boot available with men's and women's fit.**

 **2,0 mm thick high strength leather** (against abrasion, tearing and puncture). Tongue with gusset to prevent any infiltration of dust / stones.

Scuffcap TPU injected: extreme resistance at the front.

Memory Foam Titan sole for immediate and lasting comfort: antibacterial properties, respects foot hygiene.

 **Protective toe-cap:** composite HDFC.

 **Puncture-resistant midsole:** high tenacity fabric "0" penetration.



TRAILIUM PU2D antistatic sole

4 mm studs suitable for construction and heavy duty industry

Drainage channels for liquids and mud to avoid any risk of aquaplaning

Lateral edges and 15mm raised heel: reinforced grip on ladder rungs

Large bearing surface, optimal stability

Arch support and heel cushioning: MSD prevention

USAGE

- Civil engineering and Forestry works
- Logistics, automotive
- Shipyard, construction
- Petrochemistry, chemistry



lemaitre-securite.com

An exacting attitude to quality is our culture, safety our priority



NJORD S3



Standard EN ISO 20345 : 2011

Characteristics of the upper

- **Upper material:** smooth full grain water-repellent leather with abrasion-resistant TPU scuffcap material
- **Tongue/gusset:** water repellent leather
- **Collar:** water repellent leather
- **Lining:** 3D microporous fabric

Characteristics of the sole

- **Designation :** TRAILIUM PU2D
- **Material:** polyurethane / polyurethane
- **Antistatic sole**
- **SRA Adhesion coefficient:**
forward flat slip: 0,34 (standard $\geq 0,32$)
forward heel slip: 0,31 (standard $\geq 0,28$)
- **SRB Adhesion coefficient:**
forward flat slip: 0,20 (standard $\geq 0,18$)
forward heel slip: 0,17 (standard $\geq 0,13$)

VARIANT



BALDER S3 SRC
BALDS30NR

Practical information

Women fitting 35-39

Weight of one shoe size 38:
645 g

Men fitting 40-49

Weight of one shoe size 42:
725 g

Gencods

35	3237154403358	43	3237154403433
36	3237154403365	44	3237154403440
37	3237154403372	45	3237154403457
38	3237154403389	46	3237154403464
39	3237154403396	47	3237154403471
40	3237154403402	48	3237154403488
41	3237154403419	49	3237154403495
42	3237154403426		

Memo for basic and additional requirements of the standard EN ISO 20345: 2011

Safety Footwear

SBP



S1



S1P



S2



S3



200 J toe-cap: protection of the forefoot against impact and crushing.



Anti-perforation insert 1100 N: foot protection against perforation.



Anti-static footwear



Insulation against cold



Shock absorption at the heel



Insulation against heat



Fuel oil-resistant outsole



Outsole resistance to hot contact



Water penetration and water absorption resistant upper



Water resistant



Electrostatic discharge



Ankle protection



Slip-resistance on ceramic floors with detergent



Slip-resistance on steel floors with glycerol



SRC = SRA + SRB

Lemaitre Sécurité

17 rue de Bitschhoffen - CS 90024
F - 67350 Val de Moder
Tél. +33 (0)3 88 72 28 80

lemaitre-securite.com



LEMAITRE

Safety since 1974

DON_LS 04 TDS 0026
updated: 04/12/20

Member of
SINAMAP

