

Code	PB362-BLRD	
Standard	EN ISO 20345:2011 S3 SRC ESD	
Name / Description	Riley Low S3 ESD Trainer	
Weight	560 grams	
Colour	Black / Red	

Sizes	3	4	5	6	7	8	9	10	11	12	13		
-------	---	---	---	---	---	---	---	----	----	----	----	--	--

Properties	<p>Upper: Water-repellent microfiber with velour finish. Inner Lining: Abrasion Resistant, Moisture Wicking Textile. Toe Cap: Aluminium Toe Cap Resistant to 200J. Midsole: Textile Pierce Resistant Midsole – Min. 1100N. Sole Unit: Lightweight Dual Density PU/PU Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 120°C and SRC rated Slip Resistance. Footbed: Moisture Wicking, Breathable and Washable Footbed. Special Features: Technical Waterproof & Breathable Side Insert.</p>
------------	---

Areas of Application	<p>The Riley Low is suitable for any environments that specify an ESD requirement. Typical applications include electronic manufacturing, car production, chemical sites and pharmaceuticals. The extra protection across the toe area makes it perfect for jobs which involve kneeling as the microfiber is prevented from being worn away from the toe.</p>
----------------------	---

Standard	<p>EN ISO 20345:2011</p>  <p>Cat. 2</p>	S3 SRC ESD	 <p>PERF PRODUCT PERFORMANCE PASSION</p>	
----------	--	------------	---	--

Care Instructions	<p>For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.</p>
-------------------	--

Symbols	
---------	--

Contact	<p>Performance Brands Ltd The Pavilion, Bowcliffe Hall, Bramham, Wetherby. LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk</p>
---------	--