


Code	PB58C-BLK	
Standard	EN ISO 20345:2011 S3 CR HRO SRC	
Name / Description	Sharp - Cut Resistant Boot	
Weight	700 grams	
Colour	Black	

Sizes	3	4	5	6	7	8	9	10	11	12	13		
-------	---	---	---	---	---	---	---	----	----	----	----	--	--

Properties	<p>Upper: Breathable, Full Grain Leather with Textile Tongue and Collar. (Leather 1.8-2.2mm).</p> <p>Inner Lining: Cut and Abrasion Resistant, Moisture Wicking Textile.</p> <p>Toe Cap: Steel Toe Cap Resistant to 200J.</p> <p>Midsole: Stainless Steel Midsole – Min. 1100N.</p> <p>Sole Unit: Lightweight Dual Density PU/Rubber Soling System with Anti-static Properties, Shock Absorption, Heat Resistance to 300°C and SRC rated Slip Resistance.</p> <p>Footbed: Moisture Wicking, Breathable and Washable Footbed.</p>
------------	--

Areas of Application	The Cut Resistant Boot is suitable for most industrial applications. Typical applications for the cut resistant boot include glass manufacturing, waste management and engineering.
----------------------	---

Standard	EN ISO 20345:2011  Cat. 2	S3 CR HRO SRC	 PRODUCT PERFORMANCE PASSION	
----------	---	---------------------	---	--

Care Instructions	For best performance upper should be kept clean and treated regularly with a proprietary shoe polish. The sole unit should be checked regularly and kept free from debris. Footwear with obvious damage may not offer full protection and must be replaced.
-------------------	---

Symbols	
---------	--

Contact	Performance Brands Ltd, The Pavilion, Bowcliffe Hall, Bramham, Wetherby, LS23 6LP sales@performance-brands.co.uk www.performance-brands.co.uk
---------	--